

HUNGAROFASH

T-LIGHT

85 000 Watts!



NEW SOFTWARE  
Order now!

85 000 Watts!



T - L I G H T  
[www.hungaroflash.com](http://www.hungaroflash.com)

T H E F L A S H P R O D U C E R



# HUNGAROFFLASH

# T-LIGHT

## NEW PRODUCT


This is the latest model developed by Hungaroflash. T-light is only the beginning. The main power needs to be 63A/230V or phase to phase plus ground in US. The product is UL pending.

## CONTROL

It is easy for anybody to operate this unit. You can use the preprogrammed lightning effects or you can create your own in the T-LIGHT controller. We have prerecorded many waves of Thunderlights for your use. T-LIGHT is a fully rain PROOF fixture with stainless steel body. The flash length is variable from 1/24 sec to 3 Sec.

## PORTABILITY

T-LIGHT is quite small and will fit into the biggest PELI CASE container. Every unit has a second flashtube, which made by latest technology in lamp manufacture. The lamp is low pressure non-explosive XENON. The T-LIGHT unit is only 44 lbs. (20 kg)



### NAME:

### LAMP:

Maximum continuous flash discharge:  
Frequency of continuous mode:  
Flash tube type:  
Colour temperature:

### PERFORMANCES:

Intensity control  
Adjustable flash frequency

### ELECTRONIC & SAFETY DEVICES:

Electronic overdrive protection  
Overheating protection  
Indicator LED'S:

### CONTROLL SYSTEM:

2 Channel:

Nr. of addressable DMX starting addresses:  
Connection type:  
Controllability:

### POWER SUPPLY:

Nominal mains voltage:  
Operating mains voltage  
Power consumption  
Max. power draw

### FIXTURE & HOUSING:

Protection from breaking flash tube  
Fixing  
Corrosion protection  
Strobe weight: (710\*315\*250)  
Box size: (845\*530\*300) pelicase  
Box size: (820\*540\*450) paper box

### T-LIGHT

5/4,2 sec  
100/120 Hz  
special tube  
5600° Kelvin

new intelligent soft protection software  
110°C, self resetting  
Red: POWER  
Yellow: PROTECTION  
Green: DATA

DMX mode 1st.: frequency 2 nd: intensity  
HF mode 1st.:intensity 2 nd: duration  
511  
XLR 5 pole  
HF protocol, DMX 512

230/240 V - 50/60 Hz  
160-250 V - 50/60 Hz  
min.: 63 A (C or D type)  
350 A at 5 sec

Flexible tube holder  
With Doughty Trigger Clamp  
Stainless steel body  
22 Kg  
36 kg  
30 kg

Technical specifications

[www.hungaroflash.co.uk](http://www.hungaroflash.co.uk)

T H E F L A S H P R O D U C E R